

A Ramsey's Method With Pulsed Neutrons for a T-Violation Experiment

Volume 110

Number 4

July-August 2005

Y. Masuda, T. Ino, and S. Muto

High Energy Accelerator
Research Organization, 1-1 Oho,
Tsukuba Ibaraki305-0801, Japan

and

V. Skoy

Joint Institute for Nuclear
Research, 141980 Dubna,
Moscow Region, Russia

A Ramsey's method with pulsed neutrons is discussed for neutron spin manipulation in a time reversal (T) symmetry violation experiment. The neutron spin (s_n) is aligned to the direction of a vector product of the nuclear spin (I) and the neutron momentum (k_n) for the measurement of a T -odd correlation term, which is represented as $s_n \cdot (k_n \times I)$, during propagation through a polarized nuclear target. The phase control and amplitude modulation of separated oscillatory fields are discussed for the measurement of the T -odd correlation term.

Key words: polarized neutron; symmetry violation; NMR.

Accepted: August 11, 2004

Available online: <http://www.nist.gov/jres>

1. Introduction

A time reversal (T) symmetry violation has been intensively studied on polarized neutron transmission through a polarized nuclear target, since very large enhancement is expected in a T -odd term, which change sign under T [1,2,3]. The T -odd term is an angular correlation between the neutron spin (s_n), the neutron momentum (k_n) and the nuclear spin (I), which is represented as $s_n \cdot (k_n \times I)$. For the measurement of the T -odd term, the neutron spin and the nuclear spin must be polarized. At the polarization, the neutron and nuclear polarizations are aligned in magnetic fields, while the neutron polarization must be aligned vertical to the nuclear polarization for the measurement of the T -odd term. Therefore, we need a magnetic field separator, for example a superconducting sheet between two vertical magnetic fields for the neutron and the nuclear polarizations [4], or we need to rotate the neutron polar-

ization by $\pi/2$ before transmission through a polarized nuclear target as it is shown in Fig. 1. Here, we discuss a Ramsey's method [5] for the neutron spin alignment vertical to the nuclear spin.




Fig. 1. Neutron transmission experiment for the measurement of the T -odd correlation term.

2. Ramsey's Method

The Ramsey's method uses two separated oscillatory fields. The oscillating fields $2H_1 \cos \omega t$ are vertical to

the static fields H_0 which hold the neutron spin. Here, the frequency of an oscillating field is denoted as ω . The oscillating field is represented as a sum of clockwise and counterclockwise rotating fields, $H_1(\exp(i\omega t) + \exp(-i\omega t))$. In a rotating frame of a frequency ω , an effective magnetic field on the neutron spin is represented as $H_0 - \tilde{\omega}/\gamma + H_1$. At $\omega = \omega_0$, the effective field becomes H_1 and then the neutron spin rotates around H_1 . Here, $\omega_0 = \gamma H_0$. The oscillatory field is applied to the neutron spin for a time interval of t_r so that the neutron spin becomes vertical to a static field, namely the equation $\gamma H_1 t_r = \pi/2$ is satisfied as it is shown in the left hand side of Fig. 2. After the $\pi/2$ rotation, the neutron spin rotates around the static field for a time interval of t_T as it is shown in the right hand side of Fig. 2. The phase difference between the neutron spin rotation and the rotating field is represented as $\phi = -\pi/2 + (\omega_0 - \omega)t_T$. Next, the second oscillatory field, which is coherent with the first oscillatory field, is applied. In the second oscillatory field, the neutron spin rotates back to the direction of another static field as it is shown in Fig. 3. After the rotation, the angle of the neutron spin with the static field direction becomes $\phi - 3\pi/2$. The projection component of the neutron polarization P_n on the static field becomes

$$P_R = P_n \cos[(\omega_0 - \omega)t_T], \quad (1)$$

which is held by the magnetic field and then analyzed.

3. Spin Manipulation for the Measurement of the T -Odd Term

In Fig. 4, neutron spin manipulation for the measurement of the T -odd term is shown. The neutron spin is rotated in the first $\pi/2$ coil. The neutron spin is vertical




Fig. 2. Neutron spin rotation in an oscillatory field and a static field. In a rotating frame of the resonance frequency ω_0 , the neutron spin sees only an H_1 field and then rotates by $\pi/2$ under the condition $\gamma H_1 t_r = \pi/2$. After the rotation, the H_1 field is switched off and then the neutron spin rotates about the static field.




Fig. 3. Neutron spin rotation in the second oscillatory field. A plane where the neutron spin rotates under the static field rotates by $\pi/2$ under the second H_1 field.




Fig. 4. Neutron spin manipulation by Ramsey's method for the measurement of the T -odd correlation term. When the neutron exits from the first $\pi/2$ coils, the phase of the oscillatory field (rf field) is adjusted to be $\pi/2$ so that the neutron spin is aligned in the direction of $\mathbf{k}_n \times \mathbf{I}$. Here, the phase defined as 0 at the direction of $\mathbf{k}_n \times \mathbf{I}$. The phase of the second oscillatory field is adjusted to be $-\pi/2$ so that the neutron spin is rotated back to the static field.

to the rotating H_1 field upon the rotation. After the $\pi/2$ rotation, the neutron spin is placed in the plane vertical to the static field. Therefore, the neutron spin direction in the vertical plane depends upon the phase of the H_1 field. The H_1 phase must be controlled for the neutron spin alignment to the direction of $\mathbf{k}_n \times \mathbf{I}$ for the measurement of the T -odd term. In the polarized nuclear target, Larmor precession must be cancelled by pseudo-magnetic precession [6] to keep the T -odd correlation $s_n \cdot (\mathbf{k}_n \times \mathbf{I})$. After transmission through the polarized nuclear target, the neutron spin is rotated back to the static field, and then the projection component of the neutron polarization on the static field $P_n \cos(\omega t_T)$ is analyzed. As a result, the following conditions should be satisfied for the radio frequency (rf) fields.

- 1). When the neutron exits from the first and second $\pi/2$ coils, the phase of the oscillatory field (rf field) should be $\pi/2$ and $-\pi/2$, respectively, which are the angles with the direction of $\mathbf{k}_n \times \mathbf{I}$.
- 2). The value of ωt_T should be $2n\pi$ in order to obtain the largest effect.

A pulsed neutron beam from a spallation neutron source can satisfy these requirements. A typical neutron pulse width of the spallation source is $\delta t = 1 \mu\text{s}$. The variation of rf phase in the neutron pulse is $\omega\delta t$. The magnetic field strength in the nuclear spin polarizer is a key parameter. Lower magnetic field is preferable to reduce the error of the rf phase. The nuclear spin of ^{131}Xe can be polarized at a low field, for example at 0.5 mT by means of a rubidium spin exchange optical pumping. The neutron Larmor frequency is 15 kHz at 0.5 mT, therefore, the variation of the rf phase in the neutron pulse becomes

$$\omega\delta t = 15 \times 10^3 \times 2\delta \times 1 \times 10^{-6} = 0.09. \quad (2)$$

The accuracy of the neutron spin alignment with $\mathbf{k}_n \times \mathbf{I}$ is limited by the timing signal of the neutron pulse. If we use the smaller magnetic field at the $\pi/2$ coil, the uncertainty of the rf phase will be further reduced since we can use the lower rf frequency.

The ^{131}Xe nucleus has a p -wave resonance at a neutron energy of 3 eV with a resonance width of about 100 meV. The T -odd effect is largely enhanced in the p -wave resonance, therefore the measurement will be carried out in the resonance. If we place the polarized Xe target at 20 m from the neutron source, the resonance width corresponds to a neutron time of flight (TOF) width of 14 μs , and then the rf phase varies by

$$\omega\delta t = 15 \times 10^3 \times 2\delta \times 14 \times 10^{-6} = 1.3 \quad (3)$$

in the resonance. However, the variation can be analyzed by the TOF measurement and then the error of the rf phase will be reduced to the same order of error which arises from the neutron pulse timing.

The neutron TOF at 3 eV for the length of 20 cm between the two $\pi/2$ coils is about 10 μs . However, the phase difference which arises from the neutron TOF will be compensated by the phase difference between the two separated oscillatory fields.

4. Development of Pulsed Neutron Ramsey's Method

The Ramsey's method can be also applied to the measurement of pseudomagnetism. For the cancellation of the Larmor precession with the pseudomagnetic precession, we need to know the value of the pseudomagnetic field. The value is expected to be 0.5 mT at a ^{131}Xe polarization of 50 % and a ^{131}Xe pressure of 2 bar [7]. The accuracy of the cancellation is limited by the

error of the pseudomagnetism. We are developing a pulsed neutron Ramsey's method, which is shown in Fig. 5. The neutron beam is longitudinally polarized upon passing through a polarized ^3He filter. Neutron spins are rotated by $\pi/2$ from the longitudinal to transverse direction in the first $\pi/2$ coil. Xe spins are also polarized in the longitudinal direction. The neutron spins rotate around the neutron beam axis under magnetic and pseudomagnetic fields. The rotation is represented as a phase $\omega_0 t_T$. After transmission through the polarized Xe target, the neutron spins rotate back to the longitudinal direction. The projection component on the magnetic field, which is written in Eq. (1), is analyzed by the second polarized ^3He filter. The two rf fields are synchronized with the neutron pulse and their amplitudes are modulated. The amplitude modulation is proportional to $1/t_{\text{TOF}}$ so that the $\pi/2$ rotation is satisfied for different neutron energies. We can obtain the value of the pseudomagnetic field from the variation of the phase shift $\omega_0 t_T$, which is observed when the Xe polarization is switched on.




Fig. 5. Application of Ramsey's method to pseudomagnetism. The neutron beam is longitudinally polarized upon transmission through a polarized ^3He filter. The neutron polarization is rotated from the longitudinal to transverse direction. The transverse neutron polarization rotates about the longitudinal magnetic field and the pseudomagnetic field of polarized Xe. After the precession, the neutron polarization is rotated back to the longitudinal direction and then analyzed by another polarized ^3He filter.

The ^3He polarization is a key parameter. We developed the ^3He polarization by a rubidium spin exchange optical pumping in a birefringence cell, a sapphire cell [8]. The ^3He polarization was 63 % at a pressure of 3.1 bar in a cell of 3 cm inner diameter and 4.7 cm length. The neutron polarization by the ^3He cell was higher than 90 % at thermal and cold neutron energies. We can apply the ^3He cell to the pseudomagnetism measurement at these neutron energies. We also developed the Xe polarization by the optical pumping. The Xe polarization was measured by a pulsed neutron transmission. A preliminary value of ^{131}Xe polarization was 20 % [9]. The value is enough to measure the pseudomagnetism.

5. References

- [1] L. Stodolsky, Phys. Lett. **B444**, 5 (1986); Nucl. Phys. **B197**, 213 (1982).
- [2] P. K. Kabir, Phys. Rev. **D25**, 2013 (1982).
- [3] V. E. Bunakov and V. P. Gudkov, J. Phys. (Paris) Colloq. **45**, C3 (1984); JETP Lett. **36**, 329 (1982).
- [4] Y. Masuda, Neutron Res. **1**, 53 (1993).
- [5] N. F. Ramsey, Molecular Beams, Oxford University Press (1956).
- [6] V. G. Baryshevskii and M. I. Podgoretskii, Soviet Phys. JETP **20**, 704 (1964).
- [7] A. L. Barabanov, Nucl. Phys. **A614**, 1 (1997).
- [8] Y. Masuda, T. Ino, S. Muto, V. Skoy, and G. L. Jones, to be published.
- [9] V. Skoy, T. Ino, Y. Masuda, and S. Muto, to be published.